

## THERMAL TRANSFER RIBBON


Oderstraße 11 · 01109 Dresden / Germany  
Telefon ++49 351 8890891 · Fax 8805115  
graficor@aol.com

V.A.T.-Nr. DE 120807826  
Handelsregister Amtsgericht Charlottenburg HRB 92618, Geschäftsführerin: Erika Walther

### GC 31

#### Resin

GC 31 is specially designed for near-edge printers.  
Very good scratch and smudge resistance on all synthetics.  
Heat resistance up to 150°C.  
Solvent and oil resistance.



#### Ribbon Properties

Ink Type	Resin
Ribbon Thickness	8.0 µm
Base Film Material	Polyester
Base Film Thickness	4.5 µm
Ink Colour	Black
Transmission Density	More than 1.0 (Macbeth)
Recording Energy	17mJ/mm <sup>2</sup>

#### Printing Properties

Image Density	More than 1.0 (Macbeth)
Symbol Grade	More than ANSI 3.5, A (Parallel Bar Code)
Label Face Stock	Vinyl, Polyethylene, Polypropylene, Polyester
Print Speed	Up to 8 inch/sec
Usage Conditions	5°C to 35°C, 30% to 80% Relative Humidity
Storage Conditions	0°C to 40°C, 30% to 90% Relative Humidity

